

Building on the success of the Vertigo Products and on its unique StormFocus technology, the Ri70 REVELATION has been designed without any compromise to push the musical performance even further. From ultra low noise inky black background to the absolutely unsurpassed soundstage, the Ri70 sets a new standard of musical excellence for the benefit of the listener.



### Ri70 REVELATION



## FEATURES

### STORMFOCUS INTEGRATED

StormFocus is an amazing improvement in amplifier design that pushes the performance of music to unprecedented levels of accuracy and spatial resolution. You have to hear it to believe it!

### HUGE DYNAMIC CAPACITY

Each channel uses 2 amplification stages in differential mode, each of them with an independant power supply and multiple capacitors ensuring unrivaled transient response.

### SEPARATE AMPLIFIER AND PRE-AMP SECTIONS

No compromise in performance with not least than 5 separate windings for power transformer enabling each channel and preamplifier to function in complete independance..

### VIBRATION INFLUENCE TAKEN TO ITS HEIGHT

The transformer is decoupled from it's surroundings by the use of special inert material and the whole structure is supported by vibration absorbing feet. This attention to detail effectively reduces transient vibrations and other migratory acoustic parasites that affect the highly sensitive audio signal.

### EXCLUSIVE BUILD FINISH

The robust structure that houses the all-important transformer and analogue circuit is utilizing thick aluminum plates finished to a very high standard. Meticulous attention to detail is an integral part of our design philosophy and «savoir faire».

## SPECIFICATIONS

### Rated power :

2 x 125 Watts RMS / 8 ohms

### Control :

Volume, Source Selection, Sensitive Standby Switch (ambient light dimmed blue logo), StormFocus, Audio Phase Inverter, Power Switch with Live/Neutral Switch on back panel

### Remote Control :

Volume, Standby, StormFocus, Source Selection, Audio Phase Inverter, Mute

### Dimensions (L x H x P) :

440 x 120 x 410 mm  
(17.32" x 4.72" x 16.14")

### Weight :

20 kg (44 lbs)

**Guarantee :** 5 years

### Inputs :

1 Symetric XLR  
3 RCA (with volume attenuation)  
1 RCA (Bypass)  
1 External board connector

### Outputs :

1 Selector out (RCA)  
1 Pre-out (RCA)  
1 StormFocus out (RCA) (for use with another StormAudio product)  
1 Trigger out 12V

### Sensitivity / impedance input :

350 mV / 35 kΩ

### Signal to noise / ratio :

> 105 dB

### Bandwidth/pass band :

3 Hz at 200 kHz(± 1.5 dB)

### Total Harmonic distortion :

0,015 % at 1 Watt / 8 Ohms

### Power Consumption:

Max. : 650 W. / Standby : < 1 W.

## ABOUT STORMFOCUS TECHNOLOGY

StormFocus technology undoubtedly brings signal transmission (to the loudspeaker) to the next evolutionary level, enabling the musical energy to be delivered with a unique accuracy. Our technology introduces a new analog circuit design with an additional setting «StormFocus». This control allows adjustment of the energy delivered to the loudspeaker ensuring the acoustical signal is cleared of the typical phase distortions usually found in most amplifiers. This enables StormAudio amplifiers to produce a real sense of musical presence.

*StormFocus technology establishes an ultimate listening performance bringing the musical event to you.*

