

The V55 Vertigo is a statement of pure power with expression. This high range product has our exclusive and patented StormFocus technology. Immensely powerful, rich with substance, unrivalled performance and musical excellence, our promise.



V55 VERTIGO



FEATURES

STORMFOCUS INTEGRATED

StormFocus is an amazing improvement in amplifier design that pushes the performance of music to unprecedented levels of accuracy and spatial resolution. You have to hear it to believe it!

HUGE DYNAMIC CAPACITY

Left & right channels have a bank 20 capacitors ensuring a generous dynamic capacity. No compromise in performance with a huge power rating of 2 x 170W and 4 separate windings for the power supply.

SEPARATE AMPLIFIER AND PRE-AMP SECTIONS

Functioning completely independently, both mono amplifiers and pre-amp, allow your system to deliver its full potential and to evolve.

VIBRATION INFLUENCE TAKEN TO ITS HEIGHT

The transformer is decoupled from its surroundings by the use of special inert material and the whole structure is supported by three vibration absorbing feet. This attention to detail effectively reduces transient vibrations and other migratory acoustic parasites that affect the highly sensitive audio signal.

EXCLUSIVE BUILD FINISH

The robust structure that houses the all-important transformer and analogue circuit is utilizing thick aluminum plates finished to a very high standard. Meticulous attention to detail is an integral part of our design philosophy and «savoir faire».

SPECIFICATIONS

Rated Power :

2 x 170 Watts RMS / 8 ohms

Control :

Volume, Source selection, Sensitive Standby Switch on front panel, StormFocus on back panel, Power Switch on back panel

Remote Control :

Volume, Standby, Source selection, Mute

Dimensions (L x H x P) :

440 x 80 x 410 mm
(17.32' x 3.15' x 16.14')

Weight :

18 kg (39.6 lbs)

Guarantee :

5 years

Inputs :

1 Symetric XLR
4 RCA
1 Main in (RCA)

Outputs :

1 Selector out (RCA)
1 Pre-out (RCA)
1 Trigger out 12V

Sensitivity / Impedance input :

430 mV / 25 kΩ

Signal to Noise / Ratio :

> 105 dB

Bandwidth/Pass Band :

3 Hz at 150 kHz(± 1.5 dB)

Total Harmonic Distortion :

0,02 % at 1 Watt / 8 Ohms

Power Consumption:

Max. : 650 W. / Standby : < 1 W.

ABOUT STORMFOCUS TECHNOLOGY

StormFocus technology undoubtedly brings signal transmission (to the loudspeaker) to the next evolutionary level, enabling the musical energy to be delivered with a unique accuracy. Our technology introduces a new analog circuit design with an additional setting «StormFocus». This control allows adjustment of the energy delivered to the loudspeaker ensuring the acoustical signal is cleared of the typical phase distortions usually found in most amplifiers. This enables StormAudio amplifiers to produce a real sense of musical presence.

StormFocus technology establishes an ultimate listening performance bringing the musical event to you.

